

AD-A235 934



CITATION PAGE

DTIC FILE COPY

OMB No. 0704-0188

ted to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

RT DATE 1990		3. REPORT TYPE AND DATES COVERED Proceedings article	
4. TYPE AND SUBTYPE Article title: Piezoelectric Properties of 1-3 Composites of a Calcium-Modified Lead Titanate in Epoxy Resins		5. FUNDING NUMBERS P.E. #62314N Task #RJ14-T21-OT0 W.U. #59-0593-0-0 Assn #DN880-326	
6. AUTHOR(S) R. Y. Ting*; A. A. Shaulov (Bar-Ilan U., Israel); and W.A. Smith (ONR Code 1131)			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) *Materials Branch Underwater Sound Reference Detachment Naval Research Laboratory P.O. Box 568337 Orlando, FL 32856-8337		8. PERFORMING ORGANIZATION REPORT NUMBER DTIC ELECTE MAY 17 1991 C	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Technology Code 231		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES This article appeared on pp 707-710 in 1990 Ultrasonics Symposium which published the proceedings of the 4-7 Dec 90 IEEE Ultrasonics Symposium held in Honolulu.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A series of 1-3 piezocomposite samples were fabricated by using lead titanate ceramic with a dice-and-fill technique. The ceramic rods were approximately 0.10 mm in size, and the ceramic volume fraction varied from 10 to 30%. Two different epoxy resins were used. The piezoelectric d_h and g_h coefficients of the composites were found to be stable with pressure from ambient to 20 MPa. The temperature dependence of the composite properties was similar to that of the solid ceramic. The free-field voltage sensitivity of a prototype hydrophone made from the composite was calibrated and shown to be constant up to 6 kHz.			
14. SUBJECT TERMS Piezocomposites Hydrophone Lead Titanate Ceramic		15. NUMBER OF PAGES 4	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT SAR	20. LIMITATION OF ABSTRACT SAR

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet *optical scanning requirements*.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

(2)

PIEZOELECTRIC PROPERTIES OF 1-3 COMPOSITES OF A CALCIUM-MODIFIED LEAD TITANATE IN EPOXY RESINS

Robert Y. Ting^{*}, Avner A. Shaulov⁺ and Wallace A. Smith[#]

^{*}Naval Research Laboratory, P. O. Box 568337, Orlando, FL 32856

⁺Physics Department, Bar-Ilan University, Ramat-Gan 52100, Israel

[#]Office of Naval Research, Code 1131, Arlington, VA 22217

DTIC
ELECTE

MAY 17 1991

C

A series of 1-3 piezocomposite samples were fabricated by using lead titanate ceramic with a dice-and-fill technique. The ceramic rods were approximately 0.10 mm in size, and the ceramic volume fraction varied from 10 to 30%. Two different epoxy resins were used. The piezoelectric d_h and g_h coefficients of the composites were found to be stable with pressure from ambient to 20 MPa. The temperature dependence of the composite properties was similar to that of the solid ceramic. The free-field voltage sensitivity of a prototype hydrophone made from the composite was calibrated and shown to be constant up to 6 kHz.

INTRODUCTION

The development of future hull-mounted hydrophone arrays requires piezoelectric materials that exhibit high sensitivities in a hydrostatic mode far exceeding what the conventional PZT ceramics can offer. New piezoelectric composite materials with different connectivity patterns [1] were considered as potential candidates for hydrostatic-mode sensing [2]. Among different types of piezocomposites, the 1-3 type, consisting of thin parallel rods of ceramic imbedded in a polymer, was successfully developed for use in pulse-echo ultrasonic transducer arrays [3]. This success has led to an interest in considering this composite for hydrophone applications. In this paper, the piezoelectric properties of a series of 1-3 composites were investigated. Samples were fabricated by using lead titanate and two different types of epoxy resins. Their piezoelectric d_h and g_h coefficients were evaluated as a function of pressure and temperature, and a prototype

hydrophone was also assembled for evaluating the acoustic response of the composite in water. These experimental results are presented and discussed here.

EXPERIMENTAL

The ceramic used for composite fabrication was a calcium-modified lead titanate, designated as the C-24 type by Toshiba. Two epoxy polymers were used to assess the effect of polymer phase on the properties of the composite. The Stycast epoxy was stiffer than the second one, called Spurr, when both were cured at 70°C overnight. Composite samples were made by using the dice-and-fill technique [4] to form 40-mm diameter and 1-mm thick disks. Square ceramic rods were 0.10 mm in size, and ceramic volume fraction varied from 10 to 30%.

The hydrostatic d_h and g_h coefficients of each sample were determined from measurements in an acoustic coupler by using an acoustic reciprocity technique [5] at 1 kHz. This measurement frequency was selected to ensure a true hydrostatic response from the sample. The experiments covered the pressure range from ambient to 20 MPa and a temperature range of 0 - 50°C. The d_{33} coefficient of each composite sample was also measured at 100 Hz by using a Berlincourt meter. At least twenty measurements were made over the surface of the sample in order to obtain an acceptable average d_{33} value.

A 1-3 composite sample containing approximately 17% ceramic rods in Stycast epoxy was used for hydrophone fabrication. The composite sample was bonded to a 5-cm thick stainless-steel base

91 5 16 015

91-00040



plate, and the assembly was then water-proofed by encapsulation with an Eccobond resin. The prototype hydrophone was tested at a water depth of 4 m over the frequency range of 100 Hz through 100 kHz.

RESULTS AND DISCUSSION

Figure 1 shows the d_{33} and d_h coefficients for the composites as a function of lead titanate (PT) volume fraction. The data represent the experimental result obtained at room temperature and ambient pressure. Ceramic volume fraction was calculated from density measurement. The data points at the extreme right are those measured for a solid lead titanate ceramic disk. The two curves in Fig. 1 represent the result from a theoretical calculation [6] based on the simple parallel-series connectivity model of Haun and Newnham [7]. The analysis predicted a trend similar to the experimental observation, but the calculated values were approximately 10 to 20% too large.

The pressure dependence of the piezoelectric d_h and g_h coefficients for composite samples is shown in Fig. 2. The samples contained approximately 20% of lead titanate ceramic. This result suggests that these composites are remarkably stable with pressure. The property degradation for the 1-3 composites at 20 MPa is less than 0.2 dB.

In Fig. 3, the measured d_h coefficients of three composite samples are shown as a function of temperature. The d_h properties of a solid lead titanate and a PZT5 sample [8] are also included for comparison. The composite d_h coefficients are reduced from that of lead titanate, but their temperature dependence is similar to that of the pure ceramic. The material is very stable over the temperature range tested. With the softer Spurr epoxy, there is a further reduction in d_h . But, the d_h property of this composite is still comparable to that of a solid PZT5 ceramic.

Figure 4 shows the temperature dependence of the g_h coefficients of the composites. As the temperature increases, the g_h coefficients decrease gradually. When compared with the property of solid lead titanate, the slopes in this plot are approximately the same. It is believed that the

reduction in g_h is related to the increase in the permittivity ϵ_h of the sample with temperature through the relationship $g = (d/\epsilon)$.

It is also noted from Fig. 4 that the g_h coefficients increase with an increase in the ceramic volume fraction from 20 to 30%. This result is different from the prediction of an early calculation [6], which suggested that the g_h coefficients of the PT/epoxy 1-3 composite would show a maximum value at about 8% ceramic loading. This discrepancy suggests a need to improve the predictive capability of the simple parallel-series connectivity model. When compared with the pure lead titanate, the g_h coefficients are seen to have been increased by a factor of 2 or greater in the composite samples. For conventional PZT5 ceramics, the g_h values are typically in the range of 2-3 mV-m/N, as is also shown in Fig. 4. Thus, the improvement obtained in the PT/epoxy 1-3 composites is even more impressive in comparison. Since the hydrostatic sensitivity of a hydrophone is equal to the product of g_h and the thickness of the sensing element, the 1-3 composite provides a viable means to the design of sensitive new transducers for passive detection.

A prototype hydrophone was fabricated as described above by using one of the PT/Stycast 1-3 composite samples. The hydrophone was calibrated in water for its free-field voltage sensitivity over the frequency range of 100 Hz through 100 kHz. The calibration result is shown in Fig. 5. At the end of a 0.3-m cable, a constant sensitivity of about -201 dB re 1 V/ μ Pa was measured from 100 Hz to 6 kHz, a response ideal for broadband acoustic detection. At higher frequencies, different modes of the motion of the base plate began to interfere with the acoustic response of the sensor, but on the average a 4-5 dB increase in sensitivity seemed to be present. To take advantage of this high frequency behavior, a different hydrophone design will be required for the 1-3 piezocomposites.

CONCLUSION

New 1-3 piezocomposites of lead titanate and epoxy were experimentally investigated to show their stable d_h and g_h properties with pressure up

to 20 MPa. While the d_h coefficient was found to be stable with temperature, the g_h coefficient decreased slightly with temperature. A comparison of the experimental result with calculations from a simple parallel-series connectivity model indicated the need to improve the predictive capability for the performance of 1-3 composites. The role of the polymer phase was examined to show the benefit of using a stiff matrix. The result from a preliminary hydroacoustic evaluation, together with the advantages of low density and high g_h values they offer, suggest that the 1-3 piezocomposites represent a class of promising new materials for underwater acoustic applications.

REFERENCES

- [1] R. E. Newnham, D. P. Skinner and L. E. Cross, *Mat's Res. Bull.*, **13**, 525 (1978).
- [2] R. Y. Ting, *Ferroelectrics*, **67**, 143 (1986).
- [3] W. A. Smith, *Proc. 6th Intern'l Symp. Appl Ferroelectrics*, p. 249, Jun 1986, Bethlehem, PA.
- [4] H. P. Savakas, K. A. Klicker and R. E. Newnham, *Mat's Res. Bull.* **16**, 677 (1981).
- [5] R. J. Bobber, *Underwater Electroacoustic Measurements*, US Govern. Print. Office, Washington, DC, 1970.
- [6] A. A. Shaulov, W. A. Smith and R. Y. Ting, *Ferroelectrics*, **93**, 177 (1989).
- [7] M. J. Haun and R. E. Newnham, *Ferroelectrics*, **68**, 123 (1986).
- [8] K. M. Rittenmyer, R. Y. Ting and T. A. Henriquez, *J. Acous. Soc. Am.* **79**, 2073 (1986).

Accession For	
NTIS GRANT	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A1	20




Fig. 1: Piezoelectric d_{33} and d_h coefficients of 1-3 composites as a function of ceramic volume fraction.




Fig. 2: Pressure dependence of the d_h and g_h coefficients of 1-3 composites.




Fig. 3: Temperature dependence of the d_h coefficients of 1-3 composites.




Fig. 4: Temperature dependence of the g_h coefficients of 1-3 composites.




Fig. 5: Free-field voltage sensitivity of a 1-3 composite hydrophone.